

Record for the event type of Case Initiation (CaseInit)

This structure identifies the elements necessary to report a case initiation or filing event. A filing event occurs when an action is brought before the court as the result of a petition, pleading, complaint, or any other recordable action sufficient to begin the case. This definition would include an arrest or summons or other action charging an individual with a crime, as well as the filing of any other document or action recorded with the court authorized to initiate a case. The initiation of a case by whatever means is referred to as a filing event. (See AOSC14-20.)

Field	XML Element Name	Short Description	Long Description	Permissible Values	Data Type	Minimum Length	Maximum Length	Required?	Comments
Report Date/Time	evtReportDateTime	The effective date and time the information in the event record is valid.	The effective date and time the information in the event record is valid. Allows for multiple event records to be reported in the same file.	All date and date/time fields must be reported in standard ISO 8601 format using time zone offset as follows: YYYY-MM-DDTHH:MM:SS-hh:mm	datetime	25	25	M	
Event Date/Time	evtDateTime	The date and time at which the event occurred.	The date and time at which the event occurred. For Case Initiations, this is the document stamp date (physical or electronic) that the case is brought before the court through a filing event.	All date and date/time fields must be reported in standard ISO 8601 format using time zone offset as follows: YYYY-MM-DDTHH:MM:SS-hh:mm	datetime	25	25	M	Exception: The Event Date/Time field records the date and time of each case event and should be reported using standard ISO 8601 format where possible. However, many case events cannot meaningfully be reported with an associated time. If the time of an event is not available, report the date as YYYY-MM-DD. A default time of 000:00:00-00:00 will be assigned and interpreted as a missing value.
Uniform Case Number	evtUCN	Uniform Case Number (UCN)	Standard UCN to identify and update case status data as required by Fla. R. Jud. Admin. 2.245(b).		string	20	20	M	
SRS Case Type	evtSRSCaseType	The Summary Reporting System (SRS) case type at filing.	The case's SRS Case Type at the time of filing, as defined by Summary Reporting System (SRS) Manual (Jan 2002). See Appendix B, Table 4 of the Data Collection Specification for the appropriate category codes.	Only the six-digit category codes included within Appendix B, Table 4 of the Data Collection Specification are permitted.	string	6	6	M	
Divisional Assignment	evtDivisionalAssignment	The division within the local jurisdiction to which the case is assigned.	The division within the local jurisdiction to which the case is assigned. Since divisional assignments are specific to circuits and courts, clerks of court and court administration should ensure that this field is used consistently throughout the local jurisdiction.	Permissible values left to the discretion of the local jurisdiction.	string	1	120	M	Note: If the divisional assignments are associated with a team assignment, please report the team name in the Team Assigned field.
Primary Judicial Officer	<i>See four elements below for the components of a name.</i>	Name of judge or senior judge assigned primary responsibility for the case as of the Event Date/Time.	Name of judge assigned primary responsibility for the case as of the Event Date/Time. For circuits not using the Team approach. (See "team assignment" below.)	Names are separated into last name and first name, with optional middle initial, middle name, and suffix fields. See four elements below for the components of a name.	string		120	M*	*Mandatory, unless "team assigned" is used in lieu of both "Primary Judicial Officer" and "Supporting Judicial Officer".
Last Name	joFcLastName	Primary Judicial Officer's Last Name	Primary Judicial Officer's Last Name	An example would be: <joFcLastName>PEAKS</joFcLastName> <joFcFirstName>MAGDELANE</joFcFirstName> <joFcMiddleInit>S</joFcMiddleInit>	string	1	120	M	If no judge or team (see "team assignment" below) has been assigned responsibility for the case as of the date of the report, report the value "NOJUDGEASSIGNED" in both the Last Name and First Name fields. However, this value is considered a temporary assignment and the case will have to be permanently assigned as appropriate. Middle name, middle initial and suffix fields are optional and provided for flexibility in how names are stored at the local level.
First Name	joFcFirstName	Primary Judicial Officer's First Name	Primary Judicial Officer's First Name		string		120	M	
Middle Name (if applicable)	joFcMiddleName	Primary Judicial Officer's Middle Name	Primary Judicial Officer's Middle Name		string		1	O	
Middle Initial (if applicable)	joFcMiddleInit	Primary Judicial Officer's Middle Initial	Primary Judicial Officer's Middle Initial		string		1	O	
Suffix (if applicable)	joFcNameSuffix	Primary Judicial Officer's Suffix	Primary Judicial Officer's Suffix		string		6	O	
Team Assigned	evtTeamAssignment	The name for the team assigned responsibility for the case as of the Event Date/Time.	For those jurisdictions using the team concept, report a name for the team so that the appropriate group can be identified in all computations.	Permissible values left to the discretion of the local jurisdiction.	string		120	O	Optional, however "team assigned" is to be used in lieu of both "Primary Judicial Officer" and "Supporting Judicial Officer".
Supporting Judicial Officer	<i>See four elements below for the components of a name.</i>	The name of the judicial officer assigned to the case in a supporting role (if applicable) as of the Event Date/Time.	Name of the judicial officer (magistrate or designee) assigned responsibility for the case under the oversight of the Primary Judicial Officer assigned as of the Event Date/Time.	Names are separated into last name and first name, with optional middle initial, middle name, and suffix fields. See four elements below for the components of a name.	string		120	O	For those jurisdictions applying the team approach or for those cases not involving an assisting general magistrate or senior judge, this field should be left blank.
Last Name	joFcLastName	Supporting Judicial Officer's Last Name	Supporting Judicial Officer's Last Name	An example would be: <joFcLastName>PEAKS</joFcLastName> <joFcFirstName>MAGDELANE</joFcFirstName> <joFcMiddleInit>S</joFcMiddleInit>	string	1	120	M*	*If applicable to be reported, the Last Name and First Name fields are required. Middle name, middle initial and suffix fields are optional and provided for flexibility in how names are stored at the local level.
First Name	joFcFirstName	Supporting Judicial Officer's First Name	Supporting Judicial Officer's First Name		string		120	M*	
Middle Name (if applicable)	joFcMiddleName	Supporting Judicial Officer's Middle Name	Supporting Judicial Officer's Middle Name		string		1	O	
Middle Initial (if applicable)	joFcMiddleInit	Supporting Judicial Officer's Middle Initial	Supporting Judicial Officer's Middle Initial		string		1	O	
Suffix (if applicable)	joFcNameSuffix	Supporting Judicial Officer's Suffix	Supporting Judicial Officer's Suffix		string		6	O	

Record for the event type of Case Initiation (CaseInit)

This structure identifies the elements necessary to report a case initiation or filing event. A filing event occurs when an action is brought before the court as the result of a petition, pleading, complaint, or any other recordable action sufficient to begin the case. This definition would include an arrest or summons or other action charging an individual with a crime, as well as the filing of any other document or action recorded with the court authorized to initiate a case. The initiation of a case by whatever means is referred to as a filing event. (See AOSC14-20.)

Field	XML Element Name	Short Description	Long Description	Permissible Values	Data Type	Minimum Length	Maximum Length	Required?	Comments
Case Status	evtCaseStatus	The status of the case as of the Event Date/Time.	The status of the case as of the Event Date/Time.	Only two values are permitted on the reporting of a Case Initiation Event: ACTIVE or INACTIVE	string	6	20	M	Set to ACTIVE or INACTIVE. See AOSC14-20 for a description of these statuses as defined by the Case-Event Definitional Framework.
Reason for Status Change	evtReasonForStatusChange	Code categorizing the reason of a case change.	If the Case Initiation Event is submitted with an INACTIVE status, this field reports the reason for the status change from ACTIVE to INACTIVE. Permissible values are listed in Table 3 of the Data Collection Specification.	The current permissible codes are listed in Table 3 of the Data Collection Specification.	string		20	*See Comment	*Mandatory if Case Status is reported as INACTIVE. Not reported when Case Status is reported as ACTIVE.
Reason for Status Change Comment	evtReasonForStatusChangeComment	A free text description of the Reason for Status Change.	A free text description of the Reason for Status Change when a code signifying an other reason is used in the reason field. Required when the codes "OTH" OR "OTHDISP" are contained in the Reason for Status Change field. This field is not needed when one of the provided codes are used in the Reason for Status Change field.		string		200	*See Comment	*Mandatory if Reason for Status Change is reported as OTH OR OTHDISP. Not reported otherwise.
Complex Civil Litigation Flag	evtComplexCivilFlag	A flag to denote whether the case has been designated as Complex Civil Litigation.	A flag to denote whether the case has been designated as Complex Civil Litigation per Fla. R. Civ. P. 1.201. A one-character value of "Y" denotes the case has been designated as such; an "N" denotes the case has not.	Y/N	string	1	1	M	

Record for the event type of Case Closure (CaseClosure)

This structure identifies the elements necessary to report a Case Closure or disposition event.									
A disposition event has occurred when a case is closed for court activity as a result of judicial decision, order or other recordable action that provides resolution, by the court, on the issues raised by and subsequent to the filing event. (See AOSC14-20.)									
Field	XML Element Name	Short Description	Long Description	Permissible Values	Data Type	Minimum Length	Maximum Length	Required?	Comments
Report Date/Time	evtReportDateTime	The effective date and time the information in the event record is valid.	The effective date and time the information in the event record is valid. Allows for multiple event records to be reported in the same file.	All date and date/time fields must be reported in standard ISO 8601 format using time zone offset as follows: YYYY-MM-DDTHH:MM:SS-hh:mm	datetime	25	25	M	
Event Date/Time	evtDateTime	The date and time at which the event occurred.	The date and time at which the event occurred. For Case Closure and Case Reclosures, this is the date that the case was closed for court action because of a disposition event or reclosed for court action because of a reclosure event.	All date and date/time fields must be reported in standard ISO 8601 format using time zone offset as follows: YYYY-MM-DDTHH:MM:SS-hh:mm	datetime	25	25	M	Exception: The Event Date/Time field records the date and time of each case event and should be reported using standard ISO 8601 format where possible. However, many case events cannot meaningfully be reported with an associated time. If the time of an event is not available, report the date as YYYY-MM-DD. A default time of 000:00:00-00:00 will be assigned and interpreted as a missing value.
Uniform Case Number	evtUCN	Uniform Case Number (UCN)	Standard UCN to identify and update case status data as required by Fla. R. Jud. Admin. 2.245(b).		string	20	20	M	
SRS Case Type	evtSRSCaseType	The Summary Reporting System (SRS) case type at disposition.	The case's SRS Case Type at the time of disposition, as defined by Summary Reporting System (SRS) Manual (Jan 2002). See Appendix B, Table 4 of the Data Collection Specification for the appropriate category codes.	Only the six-digit category codes included within Appendix B, Table 4 of the Data Collection Specification are permitted.	string	6	6	M	This may or may not be equal to the SRS Case Type previously reported, but needs to be explicitly reported for every Case Closure event.
SRS Disposition Category	evtSRSDispCat	Disposition category as defined by Summary Reporting System (SRS) Manual. (Jan 2002)	The case's SRS Disposition category, as defined by Summary Reporting System (SRS) Manual (Jan 2002). See Appendix B, Table 5 of the Data Collection Specification for the appropriate category codes.	Only the five-digit category codes included within Appendix 5, Table 5 of the Data Collection Specification are permitted.	string	5	5	M	
Divisional Assignment	evtDivisionalAssignment	The division within the local jurisdiction to which the case is assigned.	The division within the local jurisdiction to which the case is assigned. Since divisional assignments are specific to circuits and courts, clerks of court and court administration should ensure that this field is used consistently throughout the local jurisdiction.	Permissible values left to the discretion of the local jurisdiction.	string	1	120	O	If changed since the last reported value.
Primary Judicial Officer	<i>See four elements below for the components of a name.</i>	Name of judge or senior judge assigned primary responsibility for the case as of the Event Date/Time.	Name of judge assigned primary responsibility for the case as of the Event Date/Time. For circuits not using the Team approach. (See "team assignment" below.)	Names are separated into last name and first name, with optional middle initial, middle name, and suffix fields. See four elements below for the components of a name.	string		120	O	If changed since the last reported value.
Last Name	jojcLastName	Primary Judicial Officer's Last Name	Primary Judicial Officer's Last Name	An example would be: <jojcLastName>PEAKS</jojcLastName> <jojcFirstName>MAGDELANE</jojcFirstName> <jojcMiddleInit>S</jojcMiddleInit>	string	1	120	O*	*If applicable to be reported, the Last Name and First Name fields are required. Middle name, middle initial and suffix fields are optional and provided for flexibility in how names are stored at the local level. Please note that previously-reported "NOJUDGEASSIGNED" must be updated to reflect the judge who disposed of the case.
First Name	jojcFirstName	Primary Judicial Officer's First Name	Primary Judicial Officer's First Name		string		120	O*	
Middle Name (if applicable)	jojcMiddleName	Primary Judicial Officer's Middle Name	Primary Judicial Officer's Middle Name		string		1	O	
Middle Initial (if applicable)	jojcMiddleInit	Primary Judicial Officer's Middle Initial	Primary Judicial Officer's Middle Initial		string		1	O	
Suffix (if applicable)	jojcNameSuffix	Primary Judicial Officer's Suffix	Primary Judicial Officer's Suffix		string		6	O	
Team Assigned	evtTeamAssignment	The name for the team assigned responsibility for the case as of the Event Date/Time.	For those jurisdictions using the team concept, report a name for the team so that the appropriate group can be identified in all computations.	Permissible values left to the discretion of the local jurisdiction.	string		120	O	If changed since the last reported value.
Supporting Judicial Officer	<i>See four elements below for the components of a name.</i>	The name of the judicial officer assigned to the case in a supporting role (if applicable) as of the Event Date/Time.	Name of the judicial officer (magistrate or designee) assigned responsibility for the case under the oversight of the Primary Judicial Officer assigned as of the Event Date/Time.	Names are separated into last name and first name, with optional middle initial, middle name, and suffix fields. See four elements below for the components of a name.	string		120	O	If changed since the last reported value.
Last Name	jojcLastName	Supporting Judicial Officer's Last Name	Supporting Judicial Officer's Last Name	An example would be: <jojcLastName>PEAKS</jojcLastName> <jojcFirstName>MAGDELANE</jojcFirstName> <jojcMiddleInit>S</jojcMiddleInit>	string	1	120	O*	*If applicable to be reported, the Last Name and First Name fields are required. Middle name, middle initial and suffix fields are optional and provided for flexibility in how names are stored at the local level.
First Name	jojcFirstName	Supporting Judicial Officer's First Name	Supporting Judicial Officer's First Name		string		120	O*	
Middle Name (if applicable)	jojcMiddleName	Supporting Judicial Officer's Middle Name	Supporting Judicial Officer's Middle Name		string		1	O	
Middle Initial (if applicable)	jojcMiddleInit	Supporting Judicial Officer's Middle Initial	Supporting Judicial Officer's Middle Initial		string		1	O	
Suffix (if applicable)	jojcNameSuffix	Supporting Judicial Officer's Suffix	Supporting Judicial Officer's Suffix		string		6	O	

Record for the event type of Case Closure (CaseClosure)

This structure identifies the elements necessary to report a Case Closure or disposition event.

A disposition event has occurred when a case is closed for court activity as a result of judicial decision, order or other recordable action that provides resolution, by the court, on the issues raised by and subsequent to the filing event. (See AOSC14-20.)

Field	XML Element Name	Short Description	Long Description	Permissible Values	Data Type	Minimum Length	Maximum Length	Required?	Comments
Complex Civil Litigation Flag	evtComplexCivilFlag	A flag to denote whether the case has been designated as Complex Civil Litigation.	A flag to denote whether the case has been designated as Complex Civil Litigation per Fla. R. Civ. P. 1.201. A one-character value of "Y" denotes the case has been designated as such; an "N" denotes the case has not.	Y/N	string	1	1	O	If changed since the last reported value.

Record for the event type of Case Change (CaseChange)

This structure identifies the elements necessary to report a change to any case event element. Provides for a change in any case event value(s). One or more fields can be changed within a Case Change record. Any fields not changing should not be reported in the record. Primary key: UCN.

Field	XML Element Name	Short Description	Long Description	Permissible Values	Data Type	Minimum Length	Maximum Length	Required?	Comments
Report Date/Time	evtReportDateTime	The effective date and time the information in the event record is valid.	The effective date and time the information in the event record is valid. Allows for multiple event records to be reported in the same file.	All date and date/time fields must be reported in standard ISO 8601 format using time zone offset as follows: YYYY-MM-DDTHH:MM:SS-hh:mm	datetime	25	25	M	
Event Date/Time	evtDateTime	The date and time at which the event occurred.	The date and time at which the change event occurred.	All date and date/time fields must be reported in standard ISO 8601 format using time zone offset as follows: YYYY-MM-DDTHH:MM:SS-hh:mm	datetime	25	25	M	Exception: The Event Date/Time field records the date and time of each case event and should be reported using standard ISO 8601 format where possible. However, many case events cannot meaningfully be reported with an associated time. If the time of an event is not available, report the date as YYYY-MM-DD. A default time of 000:00:00-00:00 will be assigned and interpreted as a missing value.
Uniform Case Number	evtUCN	Uniform Case Number (UCN)	Standard UCN to identify and update case status data as required by Fla. R. Jud. Admin. 2.245(b).		string	20	20	M	
SRS Case Type	evtSRSCaseType	The Summary Reporting System (SRS) case type as of the Event Date/Time.	The case's current SRS Case Type, as defined by Summary Reporting System (SRS) Manual (Jan 2002). See Appendix B, Table 4 of the Data Collection Specification for the appropriate category codes.	Only the six-digit category codes included within Appendix B, Table 4 of the Data Collection Specification are permitted.	string	6	6	O	If changed since the last reported value.
Divisional Assignment	evtDivisionalAssignment	The division within the local jurisdiction to which the case is assigned.	The division within the local jurisdiction to which the case is assigned. Since divisional assignments are specific to circuits and courts, clerks of court and court administration should ensure that this field is used consistently throughout the local jurisdiction.	Permissible values left to the discretion of the local jurisdiction.	string	1	120	O	If changed since the last reported value.
Primary Judicial Officer	<i>See four elements below for the components of a name.</i>	Name of judge or senior judge assigned primary responsibility for the case as of the Event Date/Time.	Name of judge assigned primary responsibility for the case as of the Event Date/Time. For circuits not using the Team approach. (See "team assignment" below.)	Names are separated into last name and first name, with optional middle initial, middle name, and suffix fields. See four elements below for the components of a name.	string		120	O	If changed since the last reported value.
Last Name	joFcLastName	Primary Judicial Officer's Last Name	Primary Judicial Officer's Last Name	An example would be: <joFcLastName>PEAKS</joFcLastName> <joFcFirstName>MAGDELANE</joFcFirstName> <joFcMiddleInit>S</joFcMiddleInit>	string	1	120	O*	*If applicable to be reported, the Last Name and First Name fields are required. Middle name, middle initial and suffix fields are optional and provided for flexibility in how names are stored at the local level.
First Name	joFcFirstName	Primary Judicial Officer's First Name	Primary Judicial Officer's First Name		string		120	O*	
Middle Name (if applicable)	joFcMiddleName	Primary Judicial Officer's Middle Name	Primary Judicial Officer's Middle Name		string		1	O	
Middle Initial (if applicable)	joFcMiddleInit	Primary Judicial Officer's Middle Initial	Primary Judicial Officer's Middle Initial		string		1	O	
Suffix (if applicable)	joFcNameSuffix	Primary Judicial Officer's Suffix	Primary Judicial Officer's Suffix		string		6	O	
Team Assigned	evtTeamAssignment	The name for the team assigned responsibility for the case as of the Event Date/Time.	For those jurisdictions using the team concept, report a name for the team so that the appropriate group can be identified in all computations.	Permissible values left to the discretion of the local jurisdiction.	string		120	O	Optional, however " team assigned" is to be used in lieu of both "Primary Judicial Officer" and "Supporting Judicial Officer".
Supporting Judicial Officer	<i>See four elements below for the components of a name.</i>	The name of the judicial officer assigned to the case in a supporting role (if applicable) as of the Event Date/Time.	Name of the judicial officer (magistrate or designee) assigned responsibility for the case under the oversight of the Primary Judicial Officer assigned as of the Event Date/Time.	Names are separated into last name and first name, with optional middle initial, middle name, and suffix fields. See four elements below for the components of a name.	string		120	O	For those jurisdictions applying the team approach or for those cases not involving an assisting general magistrate or senior judge, this field should be left blank.
Last Name	joFcLastName	Supporting Judicial Officer's Last Name	Supporting Judicial Officer's Last Name	An example would be: <joFcLastName>PEAKS</joFcLastName> <joFcFirstName>MAGDELANE</joFcFirstName> <joFcMiddleInit>S</joFcMiddleInit>	string	1	120	O*	*If applicable to be reported, the Last Name and First Name fields are required. Middle name, middle initial and suffix fields are optional and provided for flexibility in how names are stored at the local level.
First Name	joFcFirstName	Supporting Judicial Officer's First Name	Supporting Judicial Officer's First Name		string		120	O*	
Middle Name (if applicable)	joFcMiddleName	Supporting Judicial Officer's Middle Name	Supporting Judicial Officer's Middle Name		string		1	O	
Middle Initial (if applicable)	joFcMiddleInit	Supporting Judicial Officer's Middle Initial	Supporting Judicial Officer's Middle Initial		string		1	O	
Suffix (if applicable)	joFcNameSuffix	Supporting Judicial Officer's Suffix	Supporting Judicial Officer's Suffix		string		6	O	

Record for the event type of Case Change (CaseChange)

This structure identifies the elements necessary to report a change to any case event element. Provides for a change in any case event value(s). One or more fields can be changed within a Case Change record. Any fields not changing should not be reported in the record. Primary key: UCN.

Field	XML Element Name	Short Description	Long Description	Permissible Values	Data Type	Minimum Length	Maximum Length	Required?	Comments
Case Status	evtCaseStatus	The status of the case as of the Event Date/Time.	The status of the case as of the Event Date/Time.	Only two values are permitted on the reporting of a Case Change Event: ACTIVE or INACTIVE. Changes to CLOSED or REOPEN/RECLÖSURE are to be reported by the appropriate case event.	string	6	20	O	If changed since the last reported value.
Reason for Status Change	evtReasonForStatusChange	Code categorizing the reason of a case change.	If the Case Change Event is submitted with an INACTIVE status, this field reports the reason for the status change from ACTIVE to INACTIVE. If the Case Change Event is submitted with an ACTIVE status, this field reports the reason for the status change from INACTIVE to ACTIVE.	The current permissible codes are listed in Table 3 of the Data Collection Specification.	string		20	*See Comment	*Mandatory if Case Status is reported..
Reason for Status Change Comment	evtReasonForStatusChangeComment	A free text description of the Reason for Status Change.	A free text description of the Reason for Status Change when a code signifying an other reason is used in the reason field. Required when the codes "OTH" OR "OTHDISP" are contained in the Reason for Status Change field. This field is not needed when one of the provided codes are used in the Reason for Status Change field.		string		200	*See Comment	*Mandatory if Reason for Status Change is reported as OTH OR OTHDISP. Not reported otherwise.
Complex Civil Litigation Flag	evtComplexCivilFlag	A flag to denote whether the case has been designated as Complex Civil Litigation.	A flag to denote whether the case has been designated as Complex Civil Litigation per Fla. R. Civ. P. 1.201. A one-character value of "Y" denotes the case has been designated as such; an "N" denotes the case has not.	Y/N	string	1	1	O	If changed since the last reported value.

Record for the event type of Case Reopen (CaseReopen)

This structure identifies the elements necessary to report a case reopen event. A case reopen event occurs when a motion, pleading or other recordable action occurs on a case that requires additional court activity after a disposition event has closed the case for court activity. Note that a reopen event involves at least one action and that additional post-judgment actions may occur before the case is reclosed. (See AOSC14-20.)

Field	XML Element Name	Short Description	Long Description	Permissible Values	Data Type	Minimum Length	Maximum Length	Required?	Comments
Report Date/Time	evtReportDate/Time	The effective date and time the information in the event record is valid.	The effective date and time the information in the event record is valid. Allows for multiple event records to be reported in the same file.	All date and date/time fields must be reported in standard ISO 8601 format using time zone offset as follows: YYYY-MM-DDTHH:MM:SS-hh:mm	datetime	25	25	M	
Event Date/Time	evtDate/Time	The date and time at which the event occurred.	The date and time at which the event occurred. For Case Reopens, this is the document stamp date (physical or electronic) that the case is brought before the court through a reopen event.	All date and date/time fields must be reported in standard ISO 8601 format using time zone offset as follows: YYYY-MM-DDTHH:MM:SS-hh:mm	datetime	25	25	M	Exception: The Event Date/Time field records the date and time of each case event and should be reported using standard ISO 8601 format where possible. However, many case events cannot meaningfully be reported with an associated time. If the time of an event is not available, report the date as YYYY-MM-DD. A default time of 000:00:00-00:00 will be assigned and interpreted as a missing value.
Uniform Case Number	evtUCN	Uniform Case Number (UCN)	Standard UCN to identify and update case status data as required by Fla. R. Jud. Admin. 2.245(b).		string	20	20	M	
SRS Case Type	evtSRSCaseType	The Summary Reporting System (SRS) case type at reopen.	The case's SRS Case Type at the time of case reopen, as defined by Summary Reporting System (SRS) Manual (Jan 2002). See Appendix B, Table 4 of the Data Collection Specification for the appropriate category codes.	Only the six-digit category codes included within Appendix B, Table 4 of the Data Collection Specification are permitted.	string	6	6	M	
SRS Reopen Type	evtSRSReopenType	The Summary Reporting System (SRS) reopen type.	The case's SRS Reopen Type at the time of case reopen, as defined by Summary Reporting System (SRS) Manual (Jan 2002). See Appendix B, Table 6 of the Data Collection Specification for the appropriate category codes.	Only the five-character category codes included within Appendix B, Table 6 of the Data Collection Specification are permitted.	string	6	6	M	Note: There is currently only one Reopen Type defined for Circuit Civil division. Additional codes will be defined for the remaining divisions.
Divisional Assignment	evtDivisionalAssignment	The division within the local jurisdiction to which the case is assigned.	The division within the local jurisdiction to which the case is assigned. Since divisional assignments are specific to circuits and courts, clerks of court and court administration should ensure that this field is used consistently throughout the local jurisdiction.	Permissible values left to the discretion of the local jurisdiction.	string	1	120	M	Note: If the divisional assignments are associated with a team assignment, please report the team name in the Team Assigned field.
Primary Judicial Officer	<i>See four elements below for the components of a name.</i>	Name of judge or senior judge assigned primary responsibility for the case as of the Event Date/Time.	Name of judge assigned primary responsibility for the case as of the Event Date/Time. For circuits not using the Team approach. (See "team assignment" below.)	Names are separated into last name and first name, with optional middle initial, middle name, and suffix fields. See four elements below for the components of a name.	string		120	M*	*Mandatory, unless "team assigned" is used in lieu of both "Primary Judicial Officer" and "Supporting Judicial Officer".
Last Name	jojcLastName	Primary Judicial Officer's Last Name	Primary Judicial Officer's Last Name	An example would be: <jojcLastName>PEAKS</jojcLastName>	string	1	120	M	If no judge or team (see "team assignment" below) has been assigned responsibility for the case as of the date of the report, report the value "NOJUDGEASSIGNED" in both the Last Name and First Name fields. However, this value is considered a temporary assignment and the case will have to be permanently assigned as appropriate. Middle name, middle initial and suffix fields are optional and provided for flexibility in how names are stored at the local level.
First Name	jojcFirstName	Primary Judicial Officer's First Name	Primary Judicial Officer's First Name	<jojcFirstName>MAGDELANE</jojcFirstName>	string		120	M	
Middle Name (if applicable)	jojcMiddleName	Primary Judicial Officer's Middle Name	Primary Judicial Officer's Middle Name	<jojcMiddleName>S</jojcMiddleName>	string		1	O	
Middle Initial (if applicable)	jojcMiddleInit	Primary Judicial Officer's Middle Initial	Primary Judicial Officer's Middle Initial		string		1	O	
Suffix (if applicable)	jojcNameSuffix	Primary Judicial Officer's Suffix	Primary Judicial Officer's Suffix		string		6	O	
Team Assigned	evtTeamAssignment	The name for the team assigned responsibility for the case as of the Event Date/Time.	For those jurisdictions using the team concept, report a name for the team so that the appropriate group can be identified in all computations.	Permissible values left to the discretion of the local jurisdiction.	string		120	O	Optional, however "team assigned" is to be used in lieu of both "Primary Judicial Officer" and "Supporting Judicial Officer".
Supporting Judicial Officer	<i>See four elements below for the components of a name.</i>	The name of the judicial officer assigned to the case in a supporting role (if applicable) as of the Event Date/Time.	Name of the judicial officer (magistrate or designee) assigned responsibility for the case under the oversight of the Primary Judicial Officer assigned as of the Event Date/Time.	Names are separated into last name and first name, with optional middle initial, middle name, and suffix fields. See four elements below for the components of a name.	string		120	O	For those jurisdictions applying the team approach or for those cases not involving an assisting general magistrate or senior judge, this field should be left blank.
Last Name	jojcLastName	Supporting Judicial Officer's Last Name	Supporting Judicial Officer's Last Name	An example would be: <jojcLastName>PEAKS</jojcLastName>	string	1	120	M*	*If applicable to be reported, the Last Name and First Name fields are required. Middle name, middle initial and suffix fields are optional and provided for flexibility in how names are stored at the local level.
First Name	jojcFirstName	Supporting Judicial Officer's First Name	Supporting Judicial Officer's First Name	<jojcFirstName>MAGDELANE</jojcFirstName>	string		120	M*	
Middle Name (if applicable)	jojcMiddleName	Supporting Judicial Officer's Middle Name	Supporting Judicial Officer's Middle Name	<jojcMiddleName>S</jojcMiddleName>	string		1	O	
Middle Initial (if applicable)	jojcMiddleInit	Supporting Judicial Officer's Middle Initial	Supporting Judicial Officer's Middle Initial		string		1	O	
Suffix (if applicable)	jojcNameSuffix	Supporting Judicial Officer's Suffix	Supporting Judicial Officer's Suffix		string		6	O	

Record for the event type of Case Reopen (CaseReopen)

This structure identifies the elements necessary to report a case reopen event. A case reopen event occurs when a motion, pleading or other recordable action occurs on a case that requires additional court activity after a disposition event has closed the case for court activity. Note that a reopen event involves at least one action and that additional post-judgment actions may occur before the case is reclosed. (See AOSC14-20.)

Field	XML Element Name	Short Description	Long Description	Permissible Values	Data Type	Minimum Length	Maximum Length	Required?	Comments
Case Status	evtCaseStatus	The status of the case as of the Event Date/Time.	The status of the case as of the Event Date/Time.	Only two values are permitted on the reporting of a Case Reopen Event: REOPEN ACTIVE or REOPEN INACTIVE	string	6	20	M	Set to REOPEN ACTIVE or REOPEN INACTIVE. See AOSC14-20 for a description of these statuses as defined by the Case-Event Definitional Framework.
Reason for Status Change	evtReasonForStatusChange	Code categorizing the reason of a case change.	If the Case Initiation Event is submitted with an REOPEN INACTIVE status, this field reports the reason for the status change from REOPEN ACTIVE to REOPEN INACTIVE. Permissible values are listed in Table 3 of the Data Collection Specification.	The current permissible codes are listed in Table 3 of the Data Collection Specification.	string		20	*See Comment	*Mandatory if Case Status is reported as REOPEN INACTIVE. Not reported when Case Status is reported as REOPEN ACTIVE.
Reason for Status Change Comment	evtReasonForStatusChangeComment	A free text description of the Reason for Status Change.	A free text description of the Reason for Status Change when a code signifying an other reason is used in the reason field. Required when the codes "OTH" OR "OTHDISP" are contained in the Reason for Status Change field. This field is not needed when one of the provided codes are used in the Reason for Status Change field.		string		200	*See Comment	*Mandatory if Reason for Status Change is reported as OTH OR OTHDISP. Not reported otherwise.
Complex Civil Litigation Flag	evtComplexCivilFlag	A flag to denote whether the case has been designated as Complex Civil Litigation.	A flag to denote whether the case has been designated as Complex Civil Litigation per Fla. R. Civ. P. 1.201. A one-character value of "Y" denotes the case has been designated as such; an "N" denotes the case has not.	Y/N	string	1	1	M	

Record for the event type of Case Reclosure (CaseReclosure)

This structure identifies the elements necessary to report the closure of a reopened case or reclosure event. A case that has had one or more post-judgment actions will be considered reclosed or re-disposed (that is, in a reclosed status) for court activity on the date of the judicial decision, order or other recordable action that provides resolution to the last (or all) or the matters brought before the court since the reopen event occurred. The court, then, has no further action to take on the case. This status identifies a previously reopened case with additional matters that has been resolved by the courts and applies to the period between the reclosure event and the next reopen event. (See AOSC14-20.)

Field	XML Element Name	Short Description	Long Description	Permissible Values	Data Type	Minimum Length	Maximum Length	Required?	Comments
Report Date/Time	evtReportDateTime	The effective date and time the information in the event record is valid.	The effective date and time the information in the event record is valid. Allows for multiple event records to be reported in the same file.	All date and date/time fields must be reported in standard ISO 8601 format using time zone offset as follows: YYYY-MM-DDTHH:MM:SS-hh:mm	datetime	25	25	M	
Event Date/Time	evtDateTime	The date and time at which the event occurred.	The date and time at which the event occurred. For Case Closure and Case Reclosures, this is the date that the case was closed for court action because of a disposition event or reclosed for court action because of a reclosure event.	All date and date/time fields must be reported in standard ISO 8601 format using time zone offset as follows: YYYY-MM-DDTHH:MM:SS-hh:mm	datetime	25	25	M	Exception: The Event Date/Time field records the date and time of each case event and should be reported using standard ISO 8601 format where possible. However, many case events cannot meaningfully be reported with an associated time. If the time of an event is not available, report the date as YYY-MM-DD. A default time of 000:00:00-00:00 will be assigned and interpreted as a missing value.
Uniform Case Number	evtUCN	Uniform Case Number (UCN)	Standard UCN to identify and update case status data as required by Fla. R. Jud. Admin. 2.245(b).		string	20	20	M	
SRS Case Type	evtSRSCaseType	The Summary Reporting System (SRS) case type at reclosure.	The case's SRS Case Type at the time of reclosure, as defined by Summary Reporting System (SRS) Manual (Jan 2002). See Appendix B, Table 4 of the Data Collection Specification for the appropriate category codes.	Only the six-digit category codes included within Appendix B, Table 4 of the Data Collection Specification are permitted.	string	6	6	M	This may or may not be equal to the SRS Case Type previously reported, but needs to be explicitly reported for every Case Reclosure event.
SRS Reopen Type	evtSRSReopenType	The Summary Reporting System (SRS) reopen type at reclosure.	The case's SRS Reopen Type at the time of case reclosure, as defined by Summary Reporting System (SRS) Manual (Jan 2002). See Appendix B, Table 6 of the Data Collection Specification for the appropriate category codes.	Only the five-character category codes included within Appendix B, Table 6 of the Data Collection Specification are permitted.	string	6	6	M	This may or may not be equal to the SRS Reopen Type previously reported, but needs to be explicitly reported for every Case Reclosure event.
Divisional Assignment	evtDivisionalAssignment	The division within the local jurisdiction to which the case is assigned.	The division within the local jurisdiction to which the case is assigned. Since divisional assignments are specific to circuits and courts, clerks of court and court administration should ensure that this field is used consistently throughout the local jurisdiction.	Permissible values left to the discretion of the local jurisdiction.	string	1	120	O	If changed since the last reported value.
Primary Judicial Officer	<i>See four elements below for the components of a name.</i>	Name of judge or senior judge assigned primary responsibility for the case as of the Event Date/Time.	Name of judge assigned primary responsibility for the case as of the Event Date/Time. For circuits not using the Team approach. (See "team assignment" below.)	Names are separated into last name and first name, with optional middle initial, middle name, and suffix fields. See four elements below for the components of a name.	string		120	O	If changed since the last reported value.
Last Name	joFcLastName	Primary Judicial Officer's Last Name	Primary Judicial Officer's Last Name	An example would be: <joFcLastName>PEAKS</joFcLastName> <joFcFirstName>MAGDELANE</joFcFirstName> <joFcMiddleInit>S</joFcMiddleInit>	string	1	120	O*	*If applicable to be reported, the Last Name and First Name fields are required. Middle name, middle initial and suffix fields are optional and provided for flexibility in how names are stored at the local level. Please note that previously-reported "NOJUDGEASSIGNED" must be updated to reflect the judge who reclosed the case.
First Name	joFcFirstName	Primary Judicial Officer's First Name	Primary Judicial Officer's First Name		string		120	O*	
Middle Name (if applicable)	joFcMiddleName	Primary Judicial Officer's Middle Name	Primary Judicial Officer's Middle Name		string		1	O	
Middle Initial (if applicable)	joFcMiddleInit	Primary Judicial Officer's Middle Initial	Primary Judicial Officer's Middle Initial		string		1	O	
Suffix (if applicable)	joFcNameSuffix	Primary Judicial Officer's Suffix	Primary Judicial Officer's Suffix		string		6	O	
Team Assigned	evtTeamAssignment	The name for the team assigned responsibility for the case as of the Event Date/Time.	For those jurisdictions using the team concept, report a name for the team so that the appropriate group can be identified in all computations.	Permissible values left to the discretion of the local jurisdiction.	string		120	O	If changed since the last reported value.
Supporting Judicial Officer	<i>See four elements below for the components of a name.</i>	The name of the judicial officer assigned to the case in a supporting role (if applicable) as of the Event Date/Time.	Name of the judicial officer (magistrate or designee) assigned responsibility for the case under the oversight of the Primary Judicial Officer assigned as of the Event Date/Time.	Names are separated into last name and first name, with optional middle initial, middle name, and suffix fields. See four elements below for the components of a name.	string		120	O	If changed since the last reported value.
Last Name	joFcLastName	Supporting Judicial Officer's Last Name	Supporting Judicial Officer's Last Name	An example would be: <joFcLastName>PEAKS</joFcLastName> <joFcFirstName>MAGDELANE</joFcFirstName> <joFcMiddleInit>S</joFcMiddleInit>	string	1	120	O*	*If applicable to be reported, the Last Name and First Name fields are required. Middle name, middle initial and suffix fields are optional and provided for flexibility in how names are stored at the local level.
First Name	joFcFirstName	Supporting Judicial Officer's First Name	Supporting Judicial Officer's First Name		string		120	O*	
Middle Name (if applicable)	joFcMiddleName	Supporting Judicial Officer's Middle Name	Supporting Judicial Officer's Middle Name		string		1	O	
Middle Initial (if applicable)	joFcMiddleInit	Supporting Judicial Officer's Middle Initial	Supporting Judicial Officer's Middle Initial		string		1	O	
Suffix (if applicable)	joFcNameSuffix	Supporting Judicial Officer's Suffix	Supporting Judicial Officer's Suffix		string		6	O	

Record for the event type of Case Reclosure (CaseReclosure)

This structure identifies the elements necessary to report the closure of a reopened case or reclosure event. A case that has had one or more post-judgment actions will be considered reclosed or re-disposed (that is, in a reclosed status) for court activity on the date of the judicial decision, order or other recordable action that provides resolution to the last (or all) or the matters brought before the court since the reopen event occurred. The court, then, has no further action to take on the case. This status identifies a previously reopened case with additional matters that has been resolved by the courts and applies to the period between the reclosure event and the next reopen event. (See AOSC14-20.)

Field	XML Element Name	Short Description	Long Description	Permissible Values	Data Type	Minimum Length	Maximum Length	Required?	Comments
Complex Civil Litigation Flag	evtComplexCivilFlag	A flag to denote whether the case has been designated as Complex Civil Litigation.	A flag to denote whether the case has been designated as Complex Civil Litigation per Fla. R. Civ. P. 1.201. A one-character value of "Y" denotes the case has been designated as such; an "N" denotes the case has not.	Y/N	string	1	1	O	If changed since the last reported value.

Record for the event type of Vacated Judgement (VacatedJudgement)

This structure identifies the elements necessary to report an order vacating judgment. A vacated judgement event allows the reporting of orders directing the vacation or removal of a final judgment. The effect of this event is to nullify a previously-submitted closure event from the JDMS system and to convert all subsequent post-judgment events to periods of ACTIVE/INACTIVE status.

Field	XML Element Name	Short Description	Long Description	Permissible Values	Data Type	Minimum Length	Maximum Length	Required?	Comments
Report Date/Time	evtReportDateTime	The effective date and time the information in the event record is valid.	The effective date and time the information in the event record is valid. Allows for multiple event records to be reported in the same file.	All date and date/time fields must be reported in standard ISO 8601 format using time zone offset as follows: YYYY-MM-DDTHH:MM:SS-hh:mm	datetime	25	25	M	
Event Date/Time	evtDateTime	The date and time at which the event occurred.	The date and time at which the event occurred. For Vacated Judgements, this is the document stamp date/time from the vacating order.	All date and date/time fields must be reported in standard ISO 8601 format using time zone offset as follows: YYYY-MM-DDTHH:MM:SS-hh:mm	datetime	25	25	M	Exception: The Event Date/Time field records the date and time of each case event and should be reported using standard ISO 8601 format where possible. However, many case events cannot meaningfully be reported with an associated time. If the time of an event is not available, report the date as YYYY-MM-DD. A default time of 000:00:00-00:00 will be assigned and interpreted as a missing value.
Uniform Case Number	evtUCN	Uniform Case Number (UCN)	Standard UCN to identify and update case status data as required by Fla. R. Jud. Admin. 2.245(b).		string	20	20	M	

Record for the action type of Undo Change (UndoChange)

This structure identifies the elements necessary to delete (undo) a previously-submitted Case Change event record. An Undo Change action will delete (undo) a single Case Change event record previously reported to the system. The purpose of this action is to correct a previously-submitted Case Change event sent in error. An Undo Change action submitted with the same UCN and Event Date/Time as the original Case Change record will initiate a process to remove the specific event record. This may or may not be done preceding a second Case Change record with the correct case activity information.

Field	XML Element Name	Short Description	Long Description	Permissible Values	Data Type	Minimum Length	Maximum Length	Required?	Comments
Report Date/Time	evtReportDateTime	The effective date and time the information in the event record is valid.	The effective date and time the information in the event record is valid. Allows for multiple event records to be reported in the same file.	All date and date/time fields must be reported in standard ISO 8601 format using time zone offset as follows: YYYY-MM-DDTHH:MM:SS-hh:mm	datetime	25	25	M	
Event Date/Time	evtDateTime	The date and time at which the event needing correction occurred.	For Undo Change actions, this date must match the Event Date/Time of the previously-submitted record now identified for removal.	All date and date/time fields must be reported in standard ISO 8601 format using time zone offset as follows: YYYY-MM-DDTHH:MM:SS-hh:mm	datetime	25	25	M	Exception: The Event Date/Time field is utilized to match to the previously-submitted Case Change event record, and as such, should be reported with or without the precise time, accordingly.
Uniform Case Number	evtUCN	Uniform Case Number (UCN)	Standard UCN to identify and update case status data as required by Fla. R. Jud. Admin. 2.245(b).		string	20	20	M	

Note: Corrections to all other event records reported in error may be accomplished by re-submitting the event record with the corrected information. The event data submitted will overwrite existing event data for that UCN. Please note that all fields required for the specific event must be included in the re-submission. For example, a second Case Initiation event record submitted on a case will use the second record's date of initiation, SRS case type, primary judicial officer assigned, etc. to over-write all values submitted in the first Case Initiation record. Accordingly, all values remaining the same must be included in the re-submission.

Record for the action type of Delete Case (DeleteCase)

This structure identifies the elements necessary to delete a previously-submitted case and all case activity from the system. A Delete Case action will remove ALL records previously reported for the UCN, including all post-judgment events and will delete the case from the JDMS system. The purpose of this maintenance action is to delete a case sent in error. If a UCN should not have been reported to the UCR Project, all records can be deleted with this single action. This action is irreversible and should be used infrequently.

Field	XML Element Name	Short Description	Long Description	Permissible Values	Data Type	Minimum Length	Maximum Length	Required?	Comments
Report Date/Time	evtReportDateTime	The effective date and time the information in the event record is valid.	The effective date and time the information in the event record is valid. Allows for multiple event records to be reported in the same file.	All date and date/time fields must be reported in standard ISO 8601 format using time zone offset as follows: YYYY-MM-DDTHH:MM:SS-hh:mm	datetime	25	25	M	
Event Date/Time	evtDateTime	The date and time the case was identified for deletion.	For Delete Case actions, this is the date the entire block of case activity has been identified for deletion.	All date and date/time fields must be reported in standard ISO 8601 format using time zone offset as follows: YYYY-MM-DDTHH:MM:SS-hh:mm	datetime	25	25	M	
Uniform Case Number	evtUCN	Uniform Case Number (UCN)	Standard UCN to identify and update case status data as required by Fla. R. Jud. Admin. 2.245(b).		string	20	20	M	

Note: This action is irreversible and should be used infrequently. Caution should be taken when employing it, as numerous event records could be removed from the system by this single action. Most corrections can be accomplished by re-submitting the Case Initiation, Case Closure, Case Reopen, or Case Reclosure record with the correct information, or through the Undo Change action.

Record for the action type of Delete All Reopen Records (DeleteAllReopen)

This structure identifies the elements necessary to delete all reopen and reclosure events previously submitted for a case, without affecting the rest of the case's reported history. Similar to the Delete Case Action, a Delete All Reopen action will initiate a deletion procedure to remove ALL post-judgement activity previously reported for a UCN. All activity reported for the initial phase of the case (from Initiation to Closure) will remain in the system. The purpose of this maintenance action is to delete Reopen and Reclosure events sent in error, and can be used to remove a single event record or a block of post-judgement events. If a UCN should not have been reported as reopened after disposition, all post-judgement records can be deleted with this single action. This action is irreversible and should be used infrequently.

Field	XML Element Name	Short Description	Long Description	Permissible Values	Data Type	Minimum Length	Maximum Length	Required?	Comments
Report Date/Time	evtReportDateTime	The effective date and time the information in the event record is valid.	The effective date and time the information in the event record is valid. Allows for multiple event records to be reported in the same file.	All date and date/time fields must be reported in standard ISO 8601 format using time zone offset as follows: YYYY-MM-DDTHH:MM:SS-hh:mm	datetime	25	25	M	
Event Date/Time	evtDateTime	The date and time the reopen/reclosure activity was identified for deletion.	For Delete All Reopen actions, this is the date the entire block of case post-judgement activity has been identified for deletion.	All date and date/time fields must be reported in standard ISO 8601 format using time zone offset as follows: YYYY-MM-DDTHH:MM:SS-hh:mm	datetime	25	25	M	
Uniform Case Number	evtUCN	Uniform Case Number (UCN)	Standard UCN to identify and update case status data as required by Fla. R. Jud. Admin. 2.245(b).		string	20	20	M	

Note: This action is irreversible and should be used infrequently. Caution should be taken when employing it, as numerous event records could be removed from the system by this single action. If a case reported as reopened was an error, this action is the appropriate method to correct that error. Any other correction needed to specific data values reported in a Reopen/Reclosure event record can be initiated by re-submitting the Case Reopen or Case Reclosure record with the correct information.